From: Fisher, Sarah
To: Heller, Donald

Cc: Lam, Shelly; David Favero; "Marilyn Dedyne, GM"

Subject: RE: Allison Transmission MW-0102-S2 Report

Date: Wednesday, April 16, 2014 11:17:56 AM

Attachments: MW-0102 S2 Data Report 04-11-2014.pdf

Shelly -

Attached is the data report, minus the analytical reports. Please let me know if you would like to receive the analytical reports as well. They are around 30MB.

Thanks! Sarah

From: Heller, Donald [mailto:heller.donald@epa.gov]

Sent: Wednesday, April 16, 2014 11:43 AM

To: Fisher, Sarah

Cc: Lam, Shelly; David Favero; 'Marilyn Dedyne, GM' **Subject:** Allison Transmission MW-0102-S2 Report

Hello Sarah,

Thank you for the 4-11-14 MW-0102-S2 Area Investigation Report. Would you forward a copy to Shelly Lam?

Thanks!

Don Heller

NOTICE: This e-mail and any files transmitted with it are the property of ARCADIS U.S., Inc. and its affiliates. All rights, including without limitation copyright, are reserved. The proprietary information contained in this e-mail message, and any files transmitted with it, is intended for the use of the recipient(s) named above. If the reader of this e-mail is not the intended recipient, you are hereby notified that you have received this e-mail in error and that any review, distribution or copying of this e-mail or any files transmitted with it is strictly prohibited. If you have received this e-mail in error, please notify the sender immediately and delete the original message and any files transmitted. The unauthorized use of this e-mail or any files transmitted with it is prohibited and disclaimed by ARCADIS U.S., Inc. and its affiliates. Nothing herein is intended to constitute the offering or performance of services where otherwise restricted by law.



ARCADIS U.S., Inc.

132 East Washington Street

Suite 600 Indianapolis Indiana 46204 Tel 317.231.6500

Fax 317.231.6514

MEMO

To:

Don Heller, USEPA

Copies:

Marilyn Dedyne, General Motors LLC Sarah Fisher, ARCADIS

Teresa Colson, Allison Transmission David Favero, Favero Geosciences Francis Ramacciotti, ENVIRON

Speedway Public Library

From:

Meryl Stuckey

Heather Gastineau-Lyons

Date:

April 11, 2014

ARCADIS Project No.:

IN000473.0020

Subject:

General Motors RCRA Corrective Action at Allison Transmission, MW-0102-S2 Area Investigation, December 2013-January 2014

Summary of Additional Investigation at MW-0102-S2

As proposed in an email submitted to USEPA on November 15, 2013, and approved via e-mail by USEPA on November 15, 2013, ARCADIS, on behalf of General Motors LLC (GM), performed additional investigation in the vicinity of MW-0102-S2. Five soil borings (SB-51-1302 through SB-51-1306) and three monitoring wells (MW-1305-S2 through MW-1307-S2) were installed between December 2013 and January 2014 (Drawing 1).

Soil Boring Installation

In mid-December 2013, ARCADIS oversaw the advancement of five soil borings (SB-51-1302 through SB-51-1306). ARCADIS contracted Major Drilling Services, LLC to operate a Geoprobe to continuously sample the soil to the desired depth and sample borehole water. The soil borings were continuously logged to depth and screened using a photoionization detector (PID, 11.7ev) at two foot intervals until the till unit was encountered, at approximately 38-47 feet (ft) below ground surface (bgs). Borehole water samples were collected in the lower saturated S2 unit, five feet directly above the till unit. Boring logs are included as Attachment A.



Upon sample collection, borehole water sampling containers were immediately sealed, labeled and placed in an ice-packed cooler that was transported to Pace Analytical Services, Inc. (Pace), located in Indianapolis, Indiana, observing proper chain-of-custody procedures. The borehole water samples were analyzed for volatile organic compounds (VOCs) in accordance with USEPA SW-846 Method 8260.

Monitoring Well Installation

In January 2014, ARCADIS oversaw the installation of three new monitoring wells (MW-1305-S2 through MW-1307-S2). ARCADIS contracted Major Drilling Services, LLC to operate a Minisonic to continuously sample the soil to the desired depth and install the monitoring wells. The soil was screened using a photoionization detector (PID, 11.7ev) at two foot intervals until the till unit was encountered. Boring logs with well construction details are included as Attachment A.

Monitoring wells MW-1305-S2 and MW-1306-S2 were installed in the saturated S2 unit with 15-foot screens. These monitoring wells were installed to provide additional groundwater elevation and groundwater quality data for the newly installed recovery well (RW-1301-S2). MW-1305-S2 tested positive for Sudan IV oleophilic dye at a smear zone with odor at approximately 20 ft bgs, indicating the presence of an LNAPL. This finding is consistent with other investigation performed at this area of the Site, and LNAPL is periodically observed in other monitoring wells in the vicinity of MW-1305-S2. The observed LNAPL is the eastern extent of the diesel fuel impacts associated with AOI-40. Recovery well RW-1301-S2 was installed on November 23, 2013. Details for the recovery well installation are included in the AOI 51 Plume Extension Recovery Well Installation Report, March 31, 2014.

Monitoring well MW-1307-S2 was installed with a five foot screen in the lower saturated S2 unit. This monitoring well is located downgradient of the five newly advanced soil borings to confirm groundwater quality at the apparent leading edge of the plume.

After completion of the monitoring well installation, each well was developed using a submersible whale pump to remove any water introduced to the formation during drilling and remove any sediment from the well. The well screen was surged and the well purged using the pump until each well was free of fine material and purge water was clear.

Passive diffusion bag (PDB) samplers were deployed on January 29, 2014. During PDB deployment, the depth to water and total depth were measured in each monitoring well to ensure proper positioning (midpoint of the screen unless otherwise specified) of the PDBs. In monitoring wells MW-1305-S2 and MW-1306-S2, three PDBs were installed to vertically profile the aquifer along the 15-foot well screen (PDBs were placed at 22-24 ft bgs, 26-28 ft bgs and 30.5-32.5 ft bgs). The PDBs were allowed two weeks to equilibrate within the well and were then retrieved for sampling on February 13, 2014. No sample was able to be retrieved from the PDB bag set from 22-24 ft bgs in monitoring well MW-1305-S2. On February 13, 2014, another PDB bag was placed at the 22-24 ft interval in this monitoring well and was later sampled on February 28, 2014.



Upon sample collection, groundwater sampling containers were immediately sealed, labeled and placed in an ice-packed cooler that was transported to Pace, located in Indianapolis, Indiana, observing proper chain-of-custody procedures. The groundwater samples were analyzed for VOCs in accordance with USEPA SW-846 Method 8260.

Summary of Results

On December 19 and 20, 2013, the unvalidated analytical results for soil borings SB-51-1302 through SB-51-1306 were available and summarized in the *Interim Measures Semi-Annual Remediation Status & Groundwater Monitoring Report Second Half 2013.* Since then, the data has been validated and the validation memo is provided in Attachment B, along with the analytical results. Validated analytical results do not alter the data or use for the data submitted in the *Interim Measures Semi-Annual Remediation Status & Groundwater Monitoring Report Second Half 2013.* Trichloroethene (TCE) was reported as estimated concentrations in SB-51-1303 at 0.002 J mg/L, and in SB-51-1305 at 0.0013 J mg/L, which are both below the maximum contaminant level (MCL) of 0.005 mg/L.

On January 22, 2014, on-site recovery well RW-1301-S2 was sampled and analyzed for VOCs. Cis-1,2-dichloroethene (cis-1,2-DCE), tetrachloroethene (PCE), TCE and vinyl chloride were all detected above their respective MCLs.

Groundwater samples were collected from separate intervals within the two monitoring wells (MW-1305-S2 and MW-1306-S2) installed to provide data to aid in evaluation of the performance of the Plume Extension Groundwater Extraction System and analyzed for VOCs. PCE, TCE, cis-1,2-DCE and vinyl chloride were detected above their respective MCL in one or more intervals sampled from these monitoring wells.

In the groundwater samples collected from monitoring well MW-1306-S2, cis-1,2-DCE, 1,2,4-trichlorobenzene and vinyl chloride were detected at estimated concentrations but below their MCLs.

A groundwater sample was collected from the monitoring well (MW-1307-S2) installed to monitor the downgradient boundary of the plume extension and analyzed for VOCs. The only VOC detected in monitoring well MW-1307-S2 was TCE, at an estimated concentration of 0.0013J mg/L, which is below the MCL.

Select VOCs for many of the locations in the vicinity and downgradient from MW-0102-S2 are presented in Drawing 2 and all laboratory analytical results are provided in Attachment B. The validated analytical reports not included with this memo will be provided in the *Interim Measures Semi-Annual Remediation Status & Groundwater Monitoring Report First Half 2014*, forthcoming in July 2014.



3D Model

Geological and chemical data collected during this investigation were used to update the 3D visualization of the area in and around the southern part of Plant 12 (Model Area). The update is intended to provide data visualization to assist in understanding the geologic setting relative to the groundwater and borehole water quality data (PCE, TCE and vinyl chloride) in the Model Area. The update includes all analytical data collected to date, including the unvalidated analytical data from monitoring wells MW-1305-S2 through MW-1307-S2. Screenshots from the Mining Visualization Software (MVS) model are included as Attachment D.

Conclusions

The stratigraphy observed and the analytical results from this investigation are consistent with the information and data presented in the *MW-0102-S2 Investigation Summary* (October 2012) and the *Interim Measures Semi-Annual Remediation Status & Groundwater Monitoring Report Second Half 2013* (January 2014). The recent investigation also provides delineation of the plume extension downgradient of MW-1301-S2 to below MCLs.

It is noted that while PCE was released at AOI 51, the furthest downgradient impacts observed are cis-1,2-DCE and TCE. The low levels of TCE at SB-51-1303 (0.002 J), SB-51-1305 (0.0013J mg/L) and MW-1307-S2 (0.0013J mg/L); and only a degradation daughter concentration of cis-1,2-DCE at MW-1206-S2 (0.0031 J mg/L on October 2013) indicate that the TCE observed may have potentially resulted from a different source than the upgradient portion of the plume extension. The upgradient portion of the plume extension exhibits a different constituent signature; samples from investigation locations in the upgradient portion of the plume extension contain PCE and other degradation daughter products, in addition to TCE. One potential source of the TCE could be legacy contamination from residential use of TCE-based septic tank cleaning agents (septic tanks are understood to be present upgradient of these wells).

Based on the data and information presented herein and in the previous memos, no additional investigation is proposed for this area at this time.

Groundwater samples from monitoring wells MW-1305-S2, MW-1306-S2, and MW-1307-S2 are currently being collected for VOC analysis in April 2014. Additionally, monitoring wells installed during the calendar years of 2012 (MW-1202-S2 through MW-1207-S2) and 2013 (MW-1301-S2 and MW-1302-S2), located in the neighborhood south of MW-0102-S2, are being sampled and analyzed for VOCs in April 2014. These results will be summarized in the *Interim Measures Semi-Annual Remediation Status & Groundwater Monitoring Report First Half 2014*, due to USEPA in July 2014. Monitoring wells MW-1301-S2, MW-1302-S2, and MW-1307-S2 will be sampled again during the Fall 2014 monitoring event.



Enclosures:

Drawing 1 - MW-0102-S2 Area

Drawing 2 – Groundwater and Borehole Water VOC Analytical Results – AOI 51 South and Main Plant Perimeter


Attachment A – Boring Log and Monitoring Well Construction Diagrams


Attachment B – Laboratory Analytical Reports (on CD)

Attachment C – Drawing 10 from the *Interim Measures Semi-Annual Remediation Status & Groundwater Monitoring Report Second Half 2013*, January 2014

Attachment D - MVS Model Screenshots

DRAWINGS





ATTACHMENT A: Boring Log and Monitoring Well Construction Diagrams



BORING LOG

SB-51-1302 **BORING LOG:**

TOTAL DEPTH (ft): 44.0

GM (Allison Transmission) **Major Drilling** PROJECT: DRILLING CO.:

Speedway, IN SITE LOCATION: Ken Burkhard DRILLER:

LOGGED BY: DRILLING METHOD: Hand Auger / Direct Push **Luke Martin**

COORDINATES DATE STARTED: 12/17/2013

1649240 6 NORTHING:

DATE (COMPLETED	: 12/17/2013	NORT EAS ELEVA	STING:	1649240.6 169241.9 718.83		
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION		MOISTURE	SAMPLE NUMBER	SUDAN IV	PID (ppm)
0 ¬ •							
-		ASPHALT: Asphalt	/		SB-51-1302-01_GEO		0.0
- (FILL: FILL; angular gravel; perched water at approx	imately 0.5'.		SB-51-1302-02_GEO		0.0
-5 -		CLAY: CLAY; some sand; little silt; little gravel; hig added moisture); coarse sand to granules; angular; m perched water in clay.			SB-51-1302-03_GEO		
]			14:14.4		SB-51-1302-04_GEO		
-10 -		SAND and GRAVEL: SAND and GRAVEL; trace slarge pebbles; rounded to subangular; poorly sorted; brown to yellowish brown. 5.0-10.0' - No recovery, r	dry; loose; ock in shoe?.		SB-51-1302-05_GEO		
-10 -		18.8-19.5 - zone of fine sands, grey to yellowish bro zone is wet due to perched water at top, bottom of un	it is dry. 21.1-		SB-51-1302-06_GEO		0.0
- <mark>(</mark> -		22.3' - lens of rounded pebbles. 18.6' - Moist. 22.0' - small clay lense.	Wet. 28.9-29.0'		SB-51-1302-07_GEO		0.1
-15 - ($0 \times 0 \times 0$				SB-51-1302-08_GEO		0.1
					SB-51-1302-09_GEO		0.2
= (= .					SB-51-1302-10_GEO		0.4
-20 					SB-51-1302-11_GEO		0.6
- (SB-51-1302-12_GEO		0.9
-25 - ·					SB-51-1302-13_GEO		0.8
- (SB-51-1302-14_GEO		0.8
- <mark>(</mark>					SB-51-1302-15_GEO		0.7
-30 -					SB-51-1302-16_GEO		0.1
- <mark>(</mark>		GRAVEL and SAND: GRAVEL and SAND; silt to	very large		SB-51-1302-17_GEO		0.1
-35 -	0.1.0.1.0.1.0.1 0.1.0.1.0.1.0.1 0.1.0.1.	pebbles; rounded to subangular; poorly sorted; wet; b			SB-51-1302-18_GEO		0.1
					SB-51-1302-19_GEO		0.0
10					SB-51-1302-20_GEO	Negative at 40.5 ft	0.1
-40 -	\(\frac{1}{2} = \frac{1}{2} =	Clay: CLAY and SILT (TILL); low plasticity; trace i	ound granules.		SB-51-1302-21_GEO		0.1
-		dry; very stiff; dark grey.	ounu granuics,		SB-51-1302-22_GEO		0.0



-40 -

BORING LOG

0.6

0.5

0.4

0.6

0.5

0.5

Negative at 43.0

ft

SB-51-1303-18_GEO

SB-51-1303-19_GEO

SB-51-1303-20_GEO

SB-51-1303-21_GEO

SB-51-1303-22_GEO

SB-51-1303-23_GEO

BORING LOG-CR_51_1303

10	AI	<i>I</i> CADI3	BORING	G LOG:	SB-51-130	3	
			TOTAL	DEPTH (f	t): 45.0		
	PROJEC	CT INFORMATION		DRILLIN	G INFORMATIC	N	
PROJI	ECT: GM	(Allison Transmission)	DRILLING	CO.:			
SITE L	_OCATION:	Speedway, IN	DRILLER:		Ken Burkhard		
LOGG	ED BY:	Luke Martin	DRILLING	METHOD:	Hand Auger / Di	irect Pus	sh
DATE	STARTED:	12/18/2013	COORDIN	_			
DATE	COMPLETED	: 12/18/2013	EAS	THING: STING: ATION:	1649220.3 169215.7 719.44		
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION		MOISTURE	SAMPLE NUMBER	SUDAN IV	PID (ppm)
0 ¬				n .	00.54.4000.04.050		
=	-7-7-7-7-	ASPHALT: Asphalt			SB-51-1303-01_GEO		0.1
-	-7-7-7-7-	FILL: Fill material; angular gravel			SB-51-1303-02_GEO		0.2
-5 -	<u> </u>	CLAY and SAND: CLAY and SAND; some silt; tra slightly moist; dark brown; possible fill material. 3.9 Clay and Silt; some sand	ce gravel; ' - grading to)	SB-51-1303-03_GEO		0.2
-		SAND and GRAVEL: SAND and GRAVEL; trace s	ilt; silt to very		SB-51-1303-04_GEO		0.2
-10 -		large pebbles; round to subangular gravel; poorlly so yellowish brown. 18.7-19.0' - CLAY and SILT; som	rted; dry; loose;		SB-51-1303-05_GEO		0.2
		brown. 23.4' - moist; brown. 24.0' - Wet.			SB-51-1303-06_GEO		0.1
_					SB-51-1303-07_GEO		0.2
-15 -					SB-51-1303-08_GEO		0.1
					SB-51-1303-09_GEO		0.2
-20 -					SB-51-1303-10_GEO		0.3
-20 -					SB-51-1303-11_GEO		0.2
					SB-51-1303-12_GEO		0.4
-25 -					SB-51-1303-13_GEO		0.3
-		GRAVEL and SAND: GRAVEL and SAND; trace s large pebbles; round to subangular gravel; poorlly so			SB-51-1303-14_GEO		0.4
20		brown.	, , , ,		SB-51-1303-15_GEO		0.5
-30 -					SB-51-1303-16_GEO		0.4
=					SB-51-1303-17_GEO		0.5

Clay: CLAY and SILT (TILL); low plasticity; trace round gravels;

slightly moist; very stiff; grey.



BORING LOG

BORING LOG: **SB-51-1304**

TOTAL DEPTH (ft): **45.0**

PROJECT INFORMATION	DRILLING INFORMATION

PROJECT: GM (Allison Transmission) DRILLING CO.: Major Drilling

SITE LOCATION: Speedway, IN DRILLER: Ken Burkhard

LOGGED BY: Luke Martin DRILLING METHOD: Hand Auger / Direct Push

DATE STARTED: 12/18/2013 COORDINATES

DATE COMPLETED: 12/18/2013 EAS				THING: STING: ATION:	1649252.0 169257.9 718.50		
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION		MOISTURE	SAMPLE NUMBER	SUDAN IV	PID (ppm)
0 ¬ •					00 54 4004 04 050	1	Γ
-	_ _ _ _	ASPHALT: Asphalt	/	1	SB-51-1304-01_GEO		0.0
-	/- /- /- /- /- -/-/-/-/-/-/-	FILL: FILL; angular gravel.			SB-51-1304-02_GEO		0.2
-5 -		CLAY and SAND: CLAY and SAND; some silt; tran- pieces of brick; fine sand; slighly moist; dark brown.			SB-51-1304-03_GEO		0.1
		material for lot.			SB-51-1304-04_GEO		0.3
		SAND and GRAVEL: SAND and GRAVEL; trace s large pebbles; poorly sorted; dry; loose; yellowish br	own to grey.		SB-51-1304-05_GEO		0.2
-10 -		21.9' - Moist; brown; round to subangular gravel. 22.	.2' - Wet.		SB-51-1304-06_GEO		0.2
					SB-51-1304-07_GEO		0.3
-15 - <mark>-</mark>					SB-51-1304-08_GEO		0.2
					SB-51-1304-09_GEO		0.2
-					SB-51-1304-10_GEO		0.3
-20 -					SB-51-1304-11_GEO		0.3
=					SB-51-1304-12_GEO		0.2
-25 -					SB-51-1304-13_GEO		0.5
		GRAVEL and SAND: GRAVEL and SAND; silt to round to subangular gravel; poorly sorted; saturated;			SB-51-1304-14_GEO		0.3
-					SB-51-1304-15_GEO		0.3
-30 -					SB-51-1304-16_GEO		0.3
					SB-51-1304-17_GEO		0.4
-35 - K					SB-51-1304-18_GEO		0.4
					SB-51-1304-19_GEO		0.5
					SB-51-1304-20_GEO		0.5
-40 -					SB-51-1304-21_GEO		0.4
					SB-51-1304-22_GEO	Negative	0.4
_45] <mark>{</mark>		TILL: CLAY and SILT (TILL); low plasticity; trace granules; very stiff; slightly moist; greyish brown.	rounded		SB-51-1304-23_GEO	at 44.5	0.4



BORING LOG

BORING LOG: **SB-51-1305**

TOTAL DEPTH (ft): **45.0**

PROJECT: GM (Allison Transmission) DRILLING CO.: Major Drilling

SITE LOCATION: Speedway, IN DRILLER: Ken Burkhard

LOGGED BY: Luke Martin DRILLING METHOD: Hand Auger / Direct Push

DATE STARTED: 12/19/2013 COORDINATES

DATE COMPLETED: 12/19/2013

NORTHING: 1649190.4

EASTING: 169186.9

ELEVATION: 719.92

				ATION:	719.92		
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION		MOISTURE	SAMPLE NUMBER	SUDAN IV	PID (ppm)
0-		TOPSOIL: TOPSOIL	/	1	SB-51-1305-01_GEO		0.1
-		CLAY AND SILT: CLAY and SILT; some sand; me clay to fine sand; slightly moist; soft; brown. No add	edium plasticity;		SB-51-1305-02_GEO		0.2
-5 -	:_:_:_ 	ony to mie sana, sugmiy mons, son, orowin no add	ou moisture.		SB-51-1305-03_GEO		0.2
-					SB-51-1305-04_GEO		0.3
-		SAND and GRAVEL: SAND and GRAVEL; trace s pebbles; rounded to subangular pebbles; poorly sorte	d; dry; loose;		SB-51-1305-05_GEO		0.3
-10 -		brown to yellowish brown. 23.6' - Moist. 24.0' - Wet			SB-51-1305-06_GEO		0.2
-					SB-51-1305-07_GEO		0.2
-15 -					SB-51-1305-08_GEO		0.3
-					SB-51-1305-09_GEO		0.2
-					SB-51-1305-10_GEO		0.3
-20 -					SB-51-1305-11_GEO		0.6
-					SB-51-1305-12_GEO		1.0
-25 -					SB-51-1305-13_GEO		1.2
					SB-51-1305-14_GEO		1.6
]		GRAVEL and SAND: GRAVEL and SAND; same a	s above, but		SB-51-1305-15_GEO		1.4
-30 -		greater gravel content.	,		SB-51-1305-16_GEO		0.7
]					SB-51-1305-17_GEO		
2.5					SB-51-1305-18_GEO		1.0
-35 -					SB-51-1305-19_GEO		1.1
					SB-51-1305-20_GEO		1.3
-40 -	70 = 70 = 70 = 70 = 70 = 70 = 70 = 70 =	SAND: SAND; some gravel; fine sand to medium pe	bbles; course		SB-51-1305-21_GEO		1.7
	> · · · · · · · · · · · · · · · · · · ·	grain sand dominates; poorly sorted; wet; loose.			SB-51-1305-22_GEO	Negative	1.4
-		TILL: CLAY and SILT (TILL); low plasticity; trace gravels; slightly moist; very stiff; dark grey.	rounded		SB-51-1305-23_GEO		1.2
-45 -		1		II .	0D-01-1000-20_GEO		1.1



-45

BORING LOG

SB-51-1306-20_GEO

SB-51-1306-21_GEO

SB-51-1306-22_GEO

SB-51-1306-23_GEO

SB-51-1306-24_GEO

SB-51-1306-25_GEO

1.2

1.4

1.4

1.6

1.5

1.4

Negative at 47.0 ft

BORING LOG: **SB-51-1306**

111		ICADIS	BORING	J LUG:	2B-21-130	D					
	TOTAL				_ DEPTH (ft): 50.0						
	PROJEC	CT INFORMATION	DRILLING INFORMATION								
PROJE	ECT: GM	(Allison Transmission)	DRILLING	CO.:	Major Drilling						
SITE L	OCATION:	Speedway, IN	DRILLER:		Ken Burkhard						
LOGG	ED BY:	Luke Martin	DRILLING	METHOD:	Hand Auger / Di	rect Pus	h				
DATE COMPLETED: 12/19/2013 NOF			EAS	IATES THING: STING: ATION:	1649269.4 169278.3 717.86						
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION		MOISTURE	SAMPLE NUMBER	SUDAN IV	PID (ppm)				
0 –				V .	SB-51-1306-01_GEO						
-	_/_/_/_/_/_/	ASPHALT: Asphalt			SB-51-1306-02_GEO		0.2				
-5 -	_/_/_/_/_/_/ -/_/_/_/-	FILL: FILL, angular gravel CLAY and SAND: CLAY and SAND; some silt; tra	ce oravel:		SB-51-1306-03_GEO		0.7				
5	Ö. W.Ö. W.C	medium plasticity; slightly moist; soft; dark brown.	/	1	SB-51-1306-04_GEO		1.4				
-		SAND and GRAVEL: SAND and GRAVEL; trace s pebbles; poorly sorted; dry; loose; yellowish brown a	ilt; silt to large and grey. 7.1' -		SB-51-1306-05_GEO		1.2				
-10 -		brown. 21.1' - Moist. 21.9' - Wet.			SB-51-1306-06_GEO		1.3				
-					SB-51-1306-07_GEO		0.6				
-15 -					SB-51-1306-08_GEO		0.9				
					SB-51-1306-09_GEO		1.1				
-20 -					SB-51-1306-10_GEO		1.5				
20					SB-51-1306-11_GEO		1.4				
-					SB-51-1306-12_GEO		1.7				
-25 -					SB-51-1306-13_GEO SB-51-1306-14_GEO		1.5				
-	0000	GRAVEL and SAND: GRAVEL and SAND; trace s	ilt; same as		SB-51-1306-15_GEO		1.6				
-30 -		above, but more gravel than sand.			SB-51-1306-16_GEO		1.6				
					SB-51-1306-17_GEO		1.4				
-35 -					SB-51-1306-18_GEO		1.5				
-	0-:0-:0-:0- 0000- 0-:0-:0-:0-				SB-51-1306-19_GEO		1.2				

TILL: CLAY and SILT (TILL) encountered, but recovery is all sand

and gravel above and below small piece of till. Heaving sands from 35.0 - 50.0'. Unable to blow down past 20.0' due to compaction.



WELL CONSTRUCTION LOG

WELL NO.: **MW-1305-S2**

TOTAL DEPTH (ft):35.0

		() 2010					
	PROJE	DRILLING INFORMATION					
PROJECT: GM (Allison Transmission)			DRILLING CO.: Major Drilling				
SITE L	OCATION:	Speedway, IN	DRILLER:		Wesl	ey Cast	teel
LOGG	ED BY:	Wesley Kuhn	DRILLING N	/ETHO	D:Hand	l Auger	r / Roto Sonic
DATE	STARTED:	1/20/2014			RDINAT		
DATE	COMPLETE	ED: 1/21/2014	Northing: Easting:		9673.91 859.82	l	
			TOC Elevat				
DEPTH	SOIL	SOIL DESCRIPTION	SAMPLE	SUDAN	PID	WELI	L CONSTRUCTION
DEFIN	SYMBOLS	SOIL DESCRIPTION	ID	IV	(ppm)		DETAILS
0 ¬							
		ASPHALT: Asphalt pad	MW-1305-S2-01_GEO		0.2		Casing: PVC Sch 40 Seal: Bentonite-pellets
-		FILL: FILL; gravel road pack; clay; silts; sands; small cobbles	MW-1305-S2-02_GEO		0.2		
-		CLAY: CLAY; some silt; high to medium plasticity;	MW-1305-S2-03_GEO		0.3		
5 –	- · · · · · · · · · · · · · · · · · · ·	trace sand and pebbles; small to very large pebbles; poorly sorted; moist; dark brown (10YR 3/3)	MW-1305-S2-04_GEO		12.3		
		SAND: SAND; medium to fine grained; well sorted;	MW-1303-32-03_GEO		31.9		
-		moist; shell fragments 3.5' - dark grey (10YR 4/1) 4.5' - dark brown (10YR 3/3) 5.0' - yellowish brown (10YR 5/6)	MW-1305-S2-06_GEO		28.0		
10 -		SAND AND SILT: SAND and SILT; trace clay;	MW-1305-S2-07_GEO		20.0		
_		trace very large to small pebbles; non-plastic; loose; dry; stiff; yellowish brown (10 YR 5/4)	MW-1305-S2-08_GEO		8.8		
-		CLAY: CLAY; high to medium plasticity; trace silt; trace sand and pebbles; tacky; moist; very soft; dark			11.7		
15 –		brown (10YR 3/3)	MW-1305-S2-09_GEO		15.1		
-		SAND and GRAVEL: SAND and GRAVEL; fine grained to very large pebbles; angular to rounded	MW-1305-S2-10_GEO				
-		pebbles; poorly sorted; loose; dark yellowish brown (10YR 4/6) 20.0' - saturated; wet; smear zone; odor;	MW-1305-S2-11 GEO		8.3		Filter Pack: Sand
		staining grey; very dark greyish brown (10YR 3/2); coarse grained to very large pebbles 24.5' - trace silts	MW-1303-52-11_GEO		101.5		Screen: PVC Sch 40
20 -		and clays; stiff 25.0' - coarse grained to small cobble 27.8-28.1' - clay; some silt; medium to high	MW-1305-S2-12_GEO	Positive Sudan IV	259.3		GOLGONIA VO GON 10
		plasticity; trace small rounded pebbles; moist; yellowish brown (10YR 5/6)	MW-1305-S2-13_GEO		239.3		
-					295.8		
25 –			MW-1305-S2-14_GEO MW-1305-S2-15_GEO		90.8		
-			MW-1305-S2-16_GEO		8.7		
-			4005 00 45		25.3		
			MW-1305-S2-17_GEO		9.8		
30 -			MW-1305-S2-18_GEO				
		Clay: CLAY (TILL); some silt; no to low plasticity;	MW-1305-S2-19_GEO	Negative Sudan IV	30.8		
		trace small rounded pebbles; moist to dry; very stiff; yellowish brown (10YR 5/6) 34.2' - color change,	1505 52-19_060		11.6		
2.5		dark grey (10YR 4/1) 32.5-33.0' - sand lens; fine to medium grained; well sorted	MW-1305-S2-20_GEO		6.4	Ħ	
35 🗕			•	1			'



WELL CONSTRUCTION LOG

WELL NO.: **MW-1306-S2**

All CITY	/		TOTAL DEPTH (ft):35.0					
	PROJ	DRILLING INFORMATION						
SITE L	ECT: GM (A) OCATION:	DRILLING CO.: Major Drilling DRILLER: Wesley Casteel						
LOGGE		Wesley Kuhn	DRILLING N			_	Roto Sonic	
	STARTED: COMPLETE	1/20/2014 ED: 1/20/2014	COORDINATES: Northing: Easting:					
			TOC Elevat	SUDAN	PID	\\/_\\	CONCEDUCTION	
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION	ID	IV	(ppm)	VVELL	CONSTRUCTION DETAILS	
0								
-		TOPSOIL: TOPSOIL and grass	MW-1306-S2-01_GEO		0.0		Casing: PVC Sch 40 Seal: Bentonite-pellets	
-		CLAY AND SILT: CLAY and SILT; some sand; poorly sorted; moist; loose; dark yellowish brown (10YR 4/4) 3.0' - increase CLAY content; medium	MW-1306-S2-02_GEO		0.0			
	_: _ : _: _: _: _: _: _: _: _: _: _: _: _: _:	to high plasticity; trace sands and gravels; moist;	MW-1306-S2-03_GEO		0.0			
5 –		tacky; soft to medium stiff; dark brown (10YR 3/3) 3.5' - increase gravels; medium to very large pebbles 4.0' - increase sand content 5.0' - small cobble	MW-1306-S2-04_GEO		0.8			
-		SAND and GRAVEL: SAND and GRAVEL; medium grained to small cobbles; poorly sorted; dry to moist; very loose; yellowish brown (10YR 5/6)	MW-1306-S2-06_GEO		1.5			
10 -		18.0' - increase silt content; dry; friable; stiff (clumps) 20.0' - medium grained to very large pebbles; wet; saturated; brown (10YR 5/3) 29.5' - increase silts; medium stiff to stiff; friable	MW-1306-S2-07_GEO		1.4			
15 -			MW-1306-S2-09_GEO		1.6			
-			MW-1306-S2-10_GEO		12.8		Filter Deals Cond	
-			MW-1306-S2-11_GEO		20.1		Filter Pack: Sand Screen: PVC Sch 40	
20 –			MW-1306-S2-12_GEO	,	3.8		Screen. PVC Scr 40	
-			MW-1306-S2-13_GEO	,	6.4			
25 –			MW-1306-S2-14_GEO		7.2			
			MW-1306-S2-15_GEO		16.8			
			MW-1306-S2-16_GEO		5.8			
30 -			MW-1306-S2-17_GEO		3.9			

Negative Sudan IV

1.0

0.9

MW-1306-S2-18_GEO

MW-1306-S2-19_GEO

SAND: SAND; fine to medium grained; well sorted;

TILL: CLAY (TILL); trace silt; non-plastic; trace

rounded medium to very large pebbles; very stiff; friable; dark grey (10YR 4/1)

wet; yellowish brown (10YR 5/4)



WELL CONSTRUCTION LOG

WELL NO.: **MW-1307-S2**

TOTAL DEPTH (ft):42.0

PROJECT INFORMATION DRILLING INFORMATION


PROJECT: GM (Allison Transmission) DRILLING CO.: Major Drilling

SITE LOCATION: Speedway, IN DRILLER: Wesley Casteel

LOGGED BY: Tim Porter DRILLING METHOD: Hand Auger / Roto Sonic

	STARTED: COMPLETE	1/22/2014 ED: 1/22/2014	COORDINATES: Northing: Easting: TOC Elevation:					
DEPTH	SOIL SYMBOLS	SOIL DESCRIPTION	SAMPLE ID	SUDAN IV	PID (ppm)	WELL	CONSTRUCTION DETAILS	
0 –		ASPHALT: Asphalt pad	MW-1307-S2-01_GEO		0.8		Casing; PVC Sch 40 Seal: Bentonite-pellets	
-		FILL: FILL	MW-1307-S2-02_GEO		0.3			
5 -	/_/_/_/_/	CLAY: CLAY; clay loam; plastic; few gravels; slightly moist; dark yellowish brown (10YR 4/6)	MW-1307-S2-04_GEO		1.0			
-	-Z-Z-Z-Z-	CLAY and SAND: CLAY and SAND; loamy sand; loose; dry to slightly moist; yellowish brown (10YR 5/4)	MW-1307-S2-05_GEO		2.3			
10 -	-Z-Z-Z-Z-,	SAND and GRAVEL: SAND and GRAVEL; single	MW-1307-S2-06_GEO		0.2			
-		grained; non-cohesive; slightly moist; loose; yellowish brown (10YR 5/4) 11.0-12.5' - moist; iron oxidation; yellowish brown (10YR 5/6) 19.5-20.0' -	MW-1307-S2-07_GEO		0.9			
15 -		slightly inclusion of silt and clay 20.0' - Sand and Gravel; loose; Wet	MW-1307-S2-08_GEO		2.7			
			MW-1307-S2-19_GEO		1.0			
20 -			MW-1307-S2-11_GEO		0.7			
-			MW-1307-S2-12_GEO		1.6			
25 -			MW-1307-S2-13_GEO		0.9			
-			MW-1307-S2-14_GEO		1.0			
30 -			MW-1307-S2-15_GEO		0.9			
			MW-1307-S2-17_GEO		0.9		Filter Pack: Sand	
35 —		SAND: SAND; fine to medium grained; few silts; wet; loose; dark yellowish brown (10YR 4/4) 35.0-	MW-1307-S2-18_GEO		1.7		Screen: PVC Sch 40	
		38.0' - color change to grey (10YR 5/1)	MW-1307-S2-19_GEO	Negative	2.1			
40 -		TILL: CLAY (TILL); clayey silt; few sands and gravels; non-plastic; stiff; grey (10YR 5/1)	MW-1307-S2-20_GEO	Sudan IV	1.2			
10			GEO		0.5			

ATTACHMENT C: Drawing 10 from the *Interim Measures Semi-Annual Remediation Status* & *Groundwater Monitoring Report Second Half*2013





ATTACHMENT D: MVS MODEL SCREENSHOTS

Geologic and Contaminant Modeling

General Motors LLC at Allison Transmission Southern Portion of Plant 12

Model Area






General Model Information

- Model prepared using Mining Visualization Software (MVS).
- Geologic model includes soil borings, monitoring wells, piezometers and recovery wells installed in the subject area through 2014.
- Chemistry model includes groundwater and borehole water analytical data.



Sand and Gravel Units

View Indicator




Note: Each soil boring and/or monitoring well location used to generate the model is shown with the appropriate lithology (see symbols above)

Clay/Till Units View Indicator SAND AND GRAVEL FINE GRAINED SEDIMENT TILL

Note: Each soil boring and/or monitoring well location used to generate the model is shown with the appropriate lithology (see symbols above)

OCTOBER 2012 PCE CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October 2012 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER-NOVEMBER 2013 PCE CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October – November 2013 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2013 - JANUARY 2014 PCE CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October 2013—January 2014 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2012 PCE CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)



NOTES: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for PCE are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October 2012 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER-NOVEMBER 2013 PCE CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)



NOTES: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for PCE are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October – November 2013 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2013 - JANUARY 2014 PCE CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)



NOTES: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for PCE are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October 2013—January 2014 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2012 TCE CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October 2012 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER-NOVEMBER 2013 TCE CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October – November 2013 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2013 - JANUARY 2014 TCE CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October 2013—January 2014 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2012 TCE CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)



NOTE: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for TCE are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October 2012 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER-NOVEMBER 2013 TCE CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)



NOTE: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for TCE are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October – November 2013 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2013 - JANUARY 2014 TCE CONCENTRATIONS IN GROUNDWATER

(Looking west to east, from below)



NOTE: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for TCE are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October 2013–January 2014 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2012 VC CONCENTRATIONS IN GROUNDWATER

(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October 2012 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER-NOVEMBER 2013 VC CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October – November 2013 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2013 - JANUARY 2014 VC CONCENTRATIONS IN GROUNDWATER


(View from above showing entire depth of model)



NOTE: Recovery wells shown as magenta dot. The model is updated showing only October 2013–January 2014 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER 2012 VC CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)



NOTE: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for VC are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October 2012 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).

OCTOBER-NOVEMBER 2013 VC CONCENTRATIONS IN GROUNDWATER


(Looking west to east, from below)




NOTE: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for VC are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October – November 2013 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).


OCTOBER 2013 - JANUARY 2014 VC CONCENTRATIONS IN GROUNDWATER

(Looking west to east, from below)




NOTE: Each soil boring and/or monitoring well location used to generate the model is shown above with the appropriate lithology (see symbols above). Additionally, in each case where groundwater analytical results for VC are below detection limits, 'white' intervals are illustrated in the appropriate sample interval. The model is updated showing only October 2013—January 2014 groundwater analytical data from monitoring and recovery wells (the most recent data for this time period is used for wells sampled more than once).






(North to South Slices, from the West)




PCE CONCENTRATIONS IN GROUNDWATER WITH GEOLOGIC OVERLAY


View Indicator





(North to South Slices, from the West)


View Indicator























(West to East Slices, from the North)




(West to East Slices, from the North)




(West to East Slices, from the North)




(West to East Slices, from the North)




(West to East Slices, from the North)




(West to East Slices, from the North)



(West to East Slices, from the North)



(West to East Slices, from the North)



(West to East Slices, from the North)

